


M/V "ANYA" SHIP'S PARTICULARS

| | | | | | | | | |
|------------------------------------------------------------------------------------|--|------------------------------------------------------------------------------|-----------------------|-------------------------------|------------------------------------------------------------------------------------------------------------------------|--------------------------------------|--|------------|
|  | | | SHIP'S NAME | | ANYA | | | |
| | | | OWNER | | KAVER SHIPPING LTD TRUST COMPANY COMPLEX, AJELTAKE ROAD, AJELTEK ISLAND, MAJURO MH 96960, MARSHALL ISLANDS | | | |
| | | | MANAGING OPERATOR | | LEMISSOLER SHIPMANAGEMENT LTD. | | | |
| | | | CALL SIGN | | 5BKZ4 | | | |
| | | | FLAG | | CYPRUS | | | |
| | | | PORT OF REGISTRY | | LIMASSOL, CYPRUS | | | |
| | | | BUILT | | FEBRUARY 2017 | | | |
| | | | IMO NUMBER | | 9730268 | | | |
| | | | BUILDER | | NEW TIMES SHIPBUILDING CO. LTD, JINGJIANG CITY, CHINA | | | |
| | | | COMMUNICATION: | | | DELIVERED | | 23/02/2017 |
| SAT. PHONE BRIDGE | | +870 773 265 508 | | CLASS REGISTRATION NO | | YY 256440 | | |
| TEXT SAT "C" (LRIT) | | 421253912@stratosmobile.net | | CLASSIFIC. SOCIETY | | ABS | | |
| TEXT SAT "C" | | 421253912@stratosmobile.net | | TYPE OF VESSEL | | GEARED SUPRAMAX BULK CARRIER | | |
| SSAS SAT "C" | | 421253913@stratosmobile.net | | MAIN DIMENSIONS: | | | | |
| e-MAIL | | anya@lemissolerfleet.com | | | | | | |
| MMSI No. | | 212539000 | | L.O.A. | | 189.90 m | | |
| CARGO HOLD CAPACITY AND TANK TOP STRENGTH | | | L.B.P. | | 186.50 m | | | |
| NUMBER OF HOLDS | | 5 | | BREADTH (MOULDED) | | 32.26 m | | |
| GRAIN M ³ | | 73,467.50 m ³ | | DEPTH (MOULDED) | | 18.50 m | | |
| GRAIN FT ³ | | 2594358 ft ³ | | GROSS TONNAGE | | ABT 34,206,00 | | |
| TANK TOP STRENGTH | | 1,3,5=22t; 2,4=16t | | NETT TONNAGE | | ABT 19,510,00 | | |
| BALLAST WATER | | | SUEZ CANAL TON. | | ABT 35586.14 GT /ABT 32098.70 NT | | | |
| TOTAL | | 16,574.36 m ³ | | PANAMA CANAL TON. | | - GT / ABT 28339.00 NT | | |
| CARGO HOLD No.3 | | 14,457.90 m ³ | | AIRDRAFT:WATERLINE TO TOPMAST | | 42.10 m (normal ballast condition) | | |
| GRAND TOTAL | | 31,032.26 m ³ | | LIGHT VESSEL | | ABT 11070.50 mt | | |
| BUNKER CAPACITY | | | BUNKER CONSUMPTION | | | | | |
| H.F.O. 100% | | 1901.32 m ³ | | | | | | |
| M.G.O. 100% | | 241.26 m ³ | | LADEN: 14.0 KNOTS | | ABT 29.1 MT/DAY - AE/BOILER INCLUDED | | |
| FRESH WATER 100% | | 461.70 m ³ | | BALLAST: 14.0 KNOTS | | ABT 25.5 MT/DAY - AE/BOILER INCLUDED | | |
| DISTANCE | | | LADEN: 13.0 KNOTS | | ABT 24.5 MT/DAY - AE/BOILER INCLUDED | | | |
| DISTANCE FROM WATERLINE TO TOP OF HATCH COAMING (WLTHC) IN HEAVY BALLAST CONDITION | | #1-12.5 m #4-11.7 m | | BALLAST: 13.0 KNOTS | | ABT 21.0 MT/DAY - AE/BOILER INCLUDED | | |
| | | #2-12.2 m #5-11.5 m | | LADEN: 12.0 KNOTS | | ABT 21.5 MT/DAY - AE/BOILER INCLUDED | | |
| IN HEAVY BALLAST CONDITION | | #3-11.9 m | | BALLAST: 12.0 KNOTS | | ABT 18.5 MT/DAY - AE/BOILER INCLUDED | | |
| FROM FORE END HOLD 1 TO AFT END HOLD 2 | | 61.00 m | | IN PORT IDLE | | ABT 2.5 MT/DAY | | |
| WATERLINE TO VESSEL TOPMAST | | 42.10 m IN NORMAL BALLAST | | IN PORT WORKING | | ABT 4.1 MT/DAY | | |
| WATERLINE TO VESSEL TOPMAST | | 39.72 m IN HEAVY BALLAST | | BALLASTING/DEBALLASTING | | ABT 2.0 MT/DAY | | |
| KEEL TO TOPMAST | | 47.90 m | | MAIN ENGINE | | | | |
| KEEL TO HATCH COAMING | | 20.50 m | | MODEL | | MAN-B&W 5S60ME-C8 MAN/JAD | | |
| CARGO HANDLING GEAR | | | MAX OUTPUT BHP/KW/RPM | | 10795 BHP / 8050 KW / 89.0 RPM | | | |
| CRANES ON DECK | | MACGREGOR (4) - S.W.L. 35 mt | | NORMAL SERVICE RATING | | 8636 BHP / 6440 KW / 82.9 RPM | | |
| HATCHES | | | PROPELLER | | | | | |
| NUMBER OF HATCHES | | 5 | | DIAMETER | | 6800 mm | | |
| TYPE OF HATCH COVERS | | MACGREGOR FOLDING TYPE | | NUMBER OF BLADES | | 4 | | |
| HATCH COVER STRENGTH | | 1=4.82(t/m2); 2,3,4,5= 3.51(t/m2) | | AUXILIARY ENGINES | | | | |
| NUMBER OF HATCHES | | 5 | | NUMBER OF GENERATOR ENGINES | | 3 | | |
| TYPE OF HATCH COVERS | | MACGREGOR FOLDING TYPE | | VOLTS/HZ | | 650 KW, AC, 450V, 3Φ/60Hz | | |
| HATCH COVER STRENGTH | | 1=4.82(t/m2); 2,3,4,5= 3.51(t/m2) | | EMERGENCY GENERATOR | | #1 - 120 KW, AC, 450V, 3Φ/60Hz | | |
| DRAFTS AND DEADWEIGHT (NOT CONFIRMED YET) | | | | | | | | |
| SUMMER DRAFT | | 13.100 m | | FRBD: 5.424 m | | DWT: 58,593.10 mt | | |
| TROPICAL DRAFT | | 13.373 m | | FRBD: 5.151 m | | DWT: 60,204.80 mt | | |
| WINTER DRAFT | | 12.827 m | | FRBD: 5.697 m | | DWT: 56,983.10 mt | | |
| FRESH WATER DRAFT | | 13.395 m | | FRBD: 5.129 m | | DWT: 58,607.40 mt | | |
| TROPICAL F.W. DRAFT | | 13.668 m | | FRBD: 4.856 m | | DWT: 60,181.50 mt | | |
| | | | | | | DISPL: 69,678.10 mt | | |
| | | | | | | DISPL: 71,289.80 mt | | |
| | | | | | | DISPL: 68,068.10 mt | | |
| | | | | | | DISPL: 69,677.90 mt | | |
| | | | | | | DISPL: 71,252.00 mt | | |