


LEM VERBENA SHIP'S PARTICULARS

		SHIP'S NAME		LEM VERBENA	
		OWNER		VERICONE SHIPPING COMPANY LTD.	
		MANAGING OPERATOR		LEMISSOLER SHIPMANAGEMENT LTD.	
		CALL SIGN		V7A2547	
		FLAG		Marshall Islands	
		PORT OF REGISTRY		Majuro	
		BUILT		JUNE 2020	
		IMO NUMBER		9845829	
		BUILDER		NEW TIMES SHIPBUILDING CO. LTD, JINGJIANG CITY, CHINA	
		DELIVERED		24/07/2020	
CLASS REGISTRATION NO		YY274365			
CLASSIFIC. SOCIETY		ABS			
TYPE OF VESSEL		GEARED ULTRAMAX BULK CARRIER			
COMMUNICATION:				MAIN DIMENSIONS	
SAT. PHONE BRIDGE	NA	L.O.A.	199.90 m		
TEXT SAT "C" (LRIT)	453849020@stratosmobile.net	L.B.P.	196.50 m		
TEXT SAT "C"	NA	BREADTH (MOULDED)	32.26 m		
SSAS SAT "C"	453849021@stratosmobile.net	DEPTH (MOULDED)	18.80 m		
e-MAIL	lem.verbena@lemissolerfleet.com	GROSS TONNAGE	36781		
MMSI No.	538008591	NET TONNAGE	21527		
CARGO HOLD CAPACITY AND TANK TOP STRENGTH		SUEZ CANAL TON.	36943		
		NUMBER OF HOLDS	5		
		GRAIN M ³	78,645.5 m ³		
		GRAIN FT ³	2,777,300 ft ³		
TANK TOP STRENGTH	1,3,5=25t; 2,4=20t		PANAMA CANAL TON.		
BALLAST WATER		AIRDRAFT:WATERLINE TO TOPMAST	abt. 38.05 m		
		TOTAL	17,965.10 m ³		
		CARGO HOLD No. 3	15,599.70 m ³		
GRAND TOTAL	33,564.80 m ³		BUNKER CONSUMPTION		
BUNKER CAPACITY		LADEN: 13.5 KNOTS	ABT 26.3 MT/DAY - AE/BOILER INCLUDED		
		H.F.O. 100%	1,989.30 m ³		
		BALLAST: 13.5 KNOTS	ABT 21.1 MT/DAY - AE/BOILER INCLUDED		
		M.G.O. 100%	444.40 m ³		
FRESH WATER 100%	469.90 m ³		LADEN: 13.0 KNOTS	ABT 22.9 MT/DAY - AE/BOILER INCLUDED	
DISTANCE		BALLAST: 13.0 KNOTS	ABT 18.9 MT/DAY - AE/BOILER INCLUDED		
		DISTANCE FROM WATERLINE TO TOP OF HATCH COAMING (WLTHC) IN HEAVY BALLAST CONDITION	7.9 m		
		IN PORT IDLE	ABT 2.0 MT/DAY		
		FROM FORE END HOLD 1 TO AFT END HOLD 2	61.5 m		
		IN PORT WORKING	ABT 4.1 MT/DAY		
WATERLINE TO VESSEL TOPMAST	38.05 m		BALLASTING/DEBALLASTING	ABT 2.0 MT/DAY	
KEEL TO TOPMAST	51.55 m		MAIN ENGINE		
KEEL TO HATCH COAMING	21.40 m		MODEL	MAN B&W 7G50ME-C9.6 MAN	
CARGO HANDLING GEAR		MAX OUTPUT BHP/KW/RPM	7,500 KW / 79.0 RPM		
		CRANES ON DECK	FULL ELECTRIC (4) - SWL 36 mt		
		NORMAL SERVICE RATING	6,225 KW / 74.2 RPM		
HATCHES		PROPELLER			
		DIAMETER	6,9 m		
		NUMBER OF BLADES	4		
NUMBER OF HATCHES	5		AUXILIARY ENGINES		
TYPE OF HATCH COVERS	FOLDING TYPE		NUMBER OF GENERATOR ENGINES	3	
HATCH COVER STRENGTH t/m ²	1(6.1-6.6)3(3.43-6.13)2,4,5(3.43-3.61)		VOLTS/HZ	950 KW (1) 680 KW (2), AC, 450V, 3ø/60Hz	
DRAFTS AND DEADWEIGHT		EMERGENCY GENERATOR	120 KW, AC, 450V, 3ø/60Hz		
		SUMMER DRAFT	13.50 m		DWT: 64687.8 mt