


M/V "ELISA" SHIP'S PARTICULARS



			SHIP'S NAME		ELISA			
			OWNER		CALIMA SHIPPING LTD TRUST COMPANY COMPLEX, AJELTAKE ROAD, AJELTEK ISLAND, MAJURO MH 96960, MARSHALL ISLANDS			
			MANAGING OPERATOR		LEMISSOLER SHIPMANAGEMENT LTD.			
			CALL SIGN		V7A2527			
			FLAG		MARSHALL ISLANDS			
			PORT OF REGISTRY		MAJURO			
			BUILT		JANUARY 2016			
			IMO NUMBER		9730232			
			BUILDER		NEW TIMES SHIPBUILDING CO. LTD, JINGJIANG CITY, CHINA			
			DELIVERED		28/01/16			
COMMUNICATION:			CLASS REGISTRATION NO		117783			
SAT.PHONE BRIDGE		+870 773 935 748		CLASSIFIC. SOCIETY		DNV - GL		
TEXT SAT "C" (LRIT)		421020010@stratosmobile.net		TYPE OF VESSEL		GEARED SUPRAMAX BULK CARRIER		
TEXT SAT "C"		421020010@stratosmobile.net		MAIN DIMENSIONS:				
SSAS SAT "C"		421020011@stratosmobile.net						
e-MAIL		elisa@lemissolerfleet.com		L.O.A.		189.90 m		
MMSI No.		210200000		L.B.P.		186.50 m		
CARGO HOLD CAPACITY AND TANK TOP STRENGTH			BREADTH (MOULDED)		32.26 m			
NUMBER OF HOLDS		5		DEPTH (MOULDED)		18.50 m		
GRAIN M ³		73,467.50 m ³		GROSS TONNAGE		ABT 34.242,00		
GRAIN FT ³		2594358 ft ³		NETT TONNAGE		ABT 19.469,00		
TANK TOP STRENGTH		1,3,5=22t; 2,4=16t		SUEZ CANAL TON.		ABT 35554.60 GT /ABT 34699.63 NT		
BALLAST WATER			PANAMA CANAL TON.		- GT / ABT 28418.00 NT			
TOTAL		16,574.36 m ³		AIRDRAFT: WATERLINE TO TOPMAST		42.10 m (normal ballast condition)		
CARGO HOLD No.3		14,457.90 m ³		LIGHT VESSEL		ABT 11055.00 mt		
GRAND TOTAL		31,032.26 m ³		BUNKER CONSUMPTION				
BUNKER CAPACITY			LADEN: 14.0 KNOTS		ABT 29.1 MT/DAY - AE/BOILER INCLUDED			
H.F.O. 100%		1901.60 m ³		BALLAST: 14.0 KNOTS		ABT 25.5 MT/DAY - AE/BOILER INCLUDED		
M.G.O. 100%		241.30 m ³		LADEN: 13.0 KNOTS		ABT 24.5 MT/DAY - AE/BOILER INCLUDED		
FRESH WATER 100%		461.70 m ³		BALLAST: 13.0 KNOTS		ABT 21.0 MT/DAY - AE/BOILER INCLUDED		
DISTANCE			LADEN: 12.0 KNOTS		ABT 21.5 MT/DAY - AE/BOILER INCLUDED			
DISTANCE FROM WATERLINE TO TOP OF HATCH COAMING (WLTHC) IN HEAVY BALLAST CONDITION		#1-12.5 m #4-11.7 m		BALLAST: 12.0 KNOTS		ABT 18.5 MT/DAY - AE/BOILER INCLUDED		
		#2-12.2 m #5-11.5 m		IN PORT IDLE		ABT 2.5 MT/DAY		
		#3-11.9 m		IN PORT WORKING		ABT 4.1 MT/DAY		
FROM FORE END HOLD 1 TO AFT END HOLD 2		61.00 m		BALLASTING/DEBALLASTING		ABT 2.0 MT/DAY		
WATERLINE TO VESSEL TOPMAST			42.10 m IN NORMAL BALLAST		MAIN ENGINE			
WATERLINE TO VESSEL TOPMAST			39.72 m IN HEAVY BALLAST		MODEL		MAN-B&W 5S60ME-C8.2 MAN/JAD	
KEEL TO TOPMAST		47.90 m		MAX OUTPUT BHP/KW/RPM		10795 BHP / 8050 KW / 89.0 RPM		
KEEL TO HATCH COAMING		20.80 m		NORMAL SERVICE RATING		8636 BHP / 6440 KW / 82.6 RPM		
CARGO HANDLING GEAR			DIAMETER		6800 mm			
CRANES ON DECK		MACGREGOR (4) - S.W.L. 35 mt		NUMBER OF BLADES		4		
HATCHES			AUXILIARY ENGINES					
NUMBER OF HATCHES		5		NUMBER OF GENERATOR ENGINES		3		
TYPE OF HATCH COVERS		MACGREGOR FOLDING TYPE		VOLTS/HZ		650 KW, AC, 450V, 3Φ/60Hz		
HATCH COVER STRENGTH		1=4.82 (t/m2); 2,3,4,5= 3.51 (t/m2)		EMERGENCY GENERATOR		#1 - 120 KW, AC, 450V, 3Φ/60Hz		
DRAFTS AND DEADWEIGHT (NOT CONFIRMED YET)								
SUMMER DRAFT		13.100 m		FRBD: 5.425 m		DWT: 58,721.00 mt		
TROPICAL DRAFT		13.373 m		FRBD: 5.152 m		DWT: 60,315.05 mt		
WINTER DRAFT		12.827 m		FRBD: 5.698 m		DWT: 57,128.65 mt		
FRESH WATER DRAFT		13.395 m		FRBD: 5.130 m		DWT: 60,462.68 mt		
TROPICAL F.W. DRAFT		13.668 m		FRBD: 4.857 m		DWT: 62,076.20 mt		
						DISPL: 69,678.00 mt		
						DISPL: 71,272.05 mt		
						DISPL: 68,085.65 mt		
						DISPL: 71,419.78 mt		
						DISPL: 73,033.28 mt		